



V.1.0 GB
REV 06-07.2017.

High Performance Additives

MPEX®

PETROL LEAD REPLACEMENT

Technical Datasheet





V.1.0 GB
REV 06-07.2017.

High Performance Additives

TDS

Colour/Type	Clear / Colourless Lead Replacement
Areas of usage:	Petrol engines which use unleaded fuel but require leaded fuel.
Approvals/REF:	N/A
Environment:	Environmentally safe, does not contain lead also refer to MSDS
Packaging:	250ml Can (with a 25ml dosing chamber)
PPE:	Avoid skin contact. Refer to MSDS
Storage:	N/A
Surface prep:	None
Equipment needed:	None
Tests:	ISO9001. (For further information contact Leading Solvent Supplies Ltd)
Applying/Drying	One bottle treats 40 to 60 litres of petrol.
Origin/Manufacture:	Leading Solvent Supplies Ltd





V.1.0 GB
REV 06-07.2017.

High Performance Additives

Useful Information

How to optimise the use of MPEX® Petrol Lead Replacement

Applications:

MPEX® Petrol Lead Replacement protects valves and valve seats against wear and recession almost instantly and reduces loss of compression of engines which require leaded fuel. The elimination of valves sticking reduces maintenance costs and increases engine lifetime.

Method of use:

Pour the contents of one bottle in the fuel tank before filling it with petrol. One bottle treats 40 to 60 litres of petrol.

IMPORTANT

MPEX® Are manufactured by Leading Solvent Supplies Ltd. MPEX® products information are based on laboratory tests and practical experience. Since the conditions under which the product is used are often outside the control of Leading Solvent Supplies Ltd, we can only guarantee the product quality, since the result is dependent on the substrate, pre-treatment, temperature, air humidity, application etc. Leading Solvent Supplies Ltd reserves the right, without notice to change the product and the given data.

