

V.1.0 GB REV 06-07.2017.

**High Performance Coatings** 

# **MPEX® 650B**

# (For professional use only)

# **Technical Datasheet**







Marston Business Park | Rudgate | Tockwith | Y026 7QF | United Kingdom t. 01423 358000 | e. sales@mpexdirect.com | w. mpexdirect.com



V.1.0 GB REV 06-07.2017.

**High Performance Coatings** 

# TDS

Colour/Type	Black silky matt / Thixotropic wax based
Areas of usage:	Chassis & UBS
Environment:	Please check local requirements and SMDS
Packaging:	500ml Aerosol
PPE:	Wear dust-mask and gloves. Avoid skin contact. Refer to MSDS
Storage:	Prevent from leaking into the ground. Min/Max temp -10/+25
Surface prep:	Clean dust and grease free. Temp not below 15 degrees
Equipment needed:	N/A
Tests:	ISO9001. (For further information contact Leading Solvent Supplies Ltd)
Applying/Drying:	Shake the aerosol can for 1 minute before spraying. Approx 3-5 hours.
Origin/Manufacture:	Leading Solvent Supplies Ltd



## www.**mpexdirect**.com





V.1.0 GB REV 06-07.2017.

### High Performance Coatings

# **Useful Information**

How to optimise the use of MPEX® 650B

#### Method of use:

Clean the surface with degreaser (MPEX<sup>®</sup> 740) leave the surface or substrate to completely dry. Make sure that all MPEX<sup>®</sup> 740, is completely rinsed off with hot water.

Make sure that the surface temperature is not below 15 degrees. Mask up accordingly. Apply in minimum 400-500  $\mu m.$ 

#### **Useful tip:**

MPEX<sup>®</sup> 650B is applied by spraying. Shake the aerosol can for 1 minute before spraying. Once you have finished spraying turn the can upside down and spray briefly to clear the nozzle for future usage.

#### IMPORTANT

MPEX<sup>®</sup> Are manufactured by Leading Solvent Supplies Ltd. MPEX<sup>®</sup> products information are based on laboratory tests and practical experience. Since the conditions under which the product is used are often outside the control of Leading Solvent Supplies Ltd, we can only guarantee the product quality, since the result is dependent on the substrate, pre-treatment, temperature, air humidity, application etc. Leading Solvent Supplies Ltd reserves the right, without notice to change the product and the given data.



#### www.mpexdirect.com

