



V.1.0 GB
REV 06-07.2017.

High Performance Cleaners

MPEX[®] 780

(For professional use only)

Technical Datasheet





V.1.0 GB
REV 06-07.2017.

High Performance Cleaners

TDS

Colour/Type	Clear spray / Strong solvent based paint remover.
Areas of usage:	Any metal surface however it can remove the surface paint if applied to the same place repeatedly. Do not use on plastic. Do not allow to dry.
Environment:	Extremely flammable & hazardous for water, Please refer to MSDS.
Packaging:	500ml Aerosol
PPE:	Wear dust-mask and gloves. Avoid skin contact. Refer to MSDS.
Storage:	Approximately 12 months. Prevent from leaking into the ground. Protect from frost or direct sunlight.
Surface prep:	N/A.
Equipment needed:	N/A
Tests:	ISO9001. (For further information contact Leading Solvent Supplies Ltd)
Applying/Drying:	Shake the aerosol can for 1 minute before spraying.
Origin/Manufacture:	Leading Solvent Supplies Ltd





V.1.0 GB
REV 06-07.2017.

High Performance Cleaners

Useful Information

How to optimise the use of MPEX® 780

Applications:

MPEX® 780 is a very strong solvent based paint remover that can remove wet & semi-dry paint from metal surfaces. The product is very efficient in removing cellulose paint. Please do not use on delicate surfaces. Once the paint has been removed from the surface you must completely remove any residue with a dry absorbent cloth or tissue and don't allow it to dry.

Method of use:

Before applying MPEX® 780 we strongly recommend you test the product on an inconspicuous area before spraying. MPEX® 780 is applied by spraying onto the area containing the paint coverage that requires removing. Once applied start rubbing with a clean absorbent cloth or tissue, the paint should remove from the surface. However please be careful not to apply too much MPEX® 780 and you must ensure all the residue is removed from the surface. Due to MPEX® 780 being a strong solvent based paint remover it can also remove the paint coating from the surface underneath the spilt paint. Shake the aerosol can for 1 minute before spraying. After a short influence, clean up the surfaces with a dry, absorbent cloth. Once you have finished spraying turn the can upside down and spray briefly to clear the nozzle for future usage. The product is highly flammable and we advise you to wear a respirator mask if spraying for more than 15 minutes in one session.

IMPORTANT

MPEX® Are manufactured by Leading Solvent Supplies Ltd. MPEX® products information are based on laboratory tests and practical experience. Since the conditions under which the product is used are often outside the control of Leading Solvent Supplies Ltd, we can only guarantee the product quality, since the result is dependent on the substrate, pre-treatment, temperature, air humidity, application etc. Leading Solvent Supplies Ltd reserves the right, without notice to change the product and the given data.

www.mpexdirect.com

Marston Business Park | Rudgate | Tockwith | YO26 7QF | United Kingdom
t. 01423 358000 | e. sales@mpexdirect.com | w. [mpexdirect.com](http://www.mpexdirect.com)

LEADING
SOLVENTS

1078 LEA

