



**MILLERS OILS**

millersoils.co.uk

PRODUCT DATA SHEET  
**COMMERCIAL**  
VEHICLE



COMMERCIAL VEHICLE



DATA SHEET NO: 5752

PRODUCT NAME/VISCOSITIES:

**MULTIFLEET 15w40**

DESCRIPTION:

Multifleet 15w40 provides excellent protection for a range of Euro III and some Euro IV and Euro V vehicles and US technology vehicles. Also suitable for use in petrol engines requiring the API SL specification.

APPLICATION:

Recommended for use in diesel engines requiring a lubricant with the performance profile ACEA E7, API CI-4, MB 228.3 and Volvo VDS-3. Formulated for use in diesel engines fitted to trucks, light commercial vehicles, vans and off-highway equipment.

Multifleet 15w40, also complies to the API SL specification and can therefore be recommended for use in petrol engines. A true mixed fleet lubricant which can be used where one oil is preferred for simplicity and inventory reasons.

FEATURES AND BENEFITS:

- The mineral oil 15w40 formulation offers a high degree of engine protection and excellent oil consumption control.
- Whilst standard oil drain periods are recommended, the high levels of detergency and dispersancy ensure engine cleanliness and a reassuring performance margin at the end of the stipulated drain intervals.
- For fleet operation where diesel engines form the major part of the fleet but where it is advantageous to use the same oil in petrol engines.


SPECIFICATIONS:

- |                          |                                |
|--------------------------|--------------------------------|
| • ACEA E7                | Cummins 20071, 2, 6, 7         |
| • API CI-4, SL           | Mack EO-N (approval) EO-M Plus |
| • MB 228.3               | MAN M3275                      |
| • Volvo VDS-3 (approval) | Renault RVI RLD-2 (approval)   |
| • CAT ECF-1a, ECF-2      | MTU Type 2                     |

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)





**MILLERS OILS**

millersoils.co.uk

PRODUCT DATA SHEET

**COMMERCIAL  
VEHICLE**



COMMERCIAL VEHICLE



**TYPICAL CHARACTERISTICS:**

|                              |             |
|------------------------------|-------------|
| SAE Viscosity Grade          | 15w40       |
| Specific Gravity @ 15°C      | 0.88        |
| Kinematic Viscosity @ 100°C  | 13.75cSt    |
| Kinematic Viscosity @ 40°C   | 97.82cSt    |
| Viscosity Index              | 141         |
| Pour Point °C                | <-20        |
| Flashpoint °C                | >200        |
| Cold Crank Viscosity @ -20°C | 7,000cP max |

|                 |      |
|-----------------|------|
| TBN mg KOH / gm | 10.4 |
| Sulphated ash   | 1.39 |

**STORAGE:**

All packages should be stored indoors at ambient temperatures in a well ventilated area. Keep containers tightly closed when not in use. Where storing outside is unavoidable, barrels should be laid horizontally to avoid water ingress and to protect the product labelling and marking. Clean up any spilled material immediately. Take all necessary precautions against accidental spillage into soil or water.

**HEALTH AND SAFETY AND ENVIRONMENT:**

Health and Safety and Environmental information is provided for this product in Millers Oils Material Safety Data Sheet 5752. This gives details of any potential hazards, necessary precautions, first aid measures, environmental effects and disposal procedures.

All information relates only to the specific products designated herewith and may not be valid for this material if used in conjunction with any other materials or in any other process.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

