

according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 4941 / CAR

UFI: N4EX-HJMN-300U-31R0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

e-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha

Signal word: Warning

Pictograms:







Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 2 of 12

smoking.

P243 Take action to prevent static discharges.
P280 Wear protective gloves and eye/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:







Hazard statements

H412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | |
|------------|---|--------------------------------------|---------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (GB CLP Regulation) |) | | |
| 64742-49-0 | Hydrocarbons, C9-C10, n-alkanes, | isoalkanes, cyclics, <2% aromatics | | 20 - < 25 % |
| | 927-241-2 | | 01-2119471843-32 | |
| | Flam. Liq. 3, STOT SE 3, Asp. Tox | . 1, Aquatic Chronic 3; H226 H336 H | 304 H412 | |
| 64742-95-6 | Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | | | 10 - < 15 % |
| | 918-668-5 | | 01-2119455851-35 | |
| | Flam. Liq. 3, STOT SE 3, STOT SE H411 | | | |
| 64742-82-1 | naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha | | | 5 - < 10 % |
| | 919-446-0 | | 01-2119458049-33 | |
| | Flam. Liq. 3, STOT SE 3, STOT RE H411 | 1, Asp. Tox. 1, Aquatic Chronic 2; F | H226 H336 H372 H304 | |
| 108-32-7 | propylene carbonate | 1 - < 5 % | | |
| | 203-572-1 | 607-194-00-1 | 01-2119537232-48 | |
| | Eye Irrit. 2; H319 | | | |

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 3 of 12

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|--------------------------|---|-------------|
| | Specific Conc. | Limits, M-factors and ATE | |
| 64742-49-0 | 927-241-2 | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics | 20 - < 25 % |
| | inhalation: LC | 50 = 4951 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 4951 mg/kg | |
| 64742-95-6 | 918-668-5 | Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | 10 - < 15 % |
| | inhalation: LC: mg/kg | 50 = >6193 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = 3492 | |
| 64742-82-1 | 919-446-0 | naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha | 5 - < 10 % |
| | dermal: LD50 | = 3400 mg/kg; oral: LD50 = >15000 mg/kg | |
| 108-32-7 | 203-572-1 | propylene carbonate | 1 - < 5 % |
| | dermal: LD50 | = > 20000 mg/kg; oral: LD50 = 33520 mg/kg | |

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

In case of fire, use sand, extinguishing powder or alcohol resistant foam.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, toxic



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 4 of 12

5.3. Advice for firefighters

Wear respiratory protection.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil.

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Use only in well-ventilated areas.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 5 of 12

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Not required.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|---|-----------------------|----------|------------------|
| DNEL type | | Exposure route | Effect | Value |
| 64742-49-0 | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% | % aromatics | | |
| Worker DNEL, | long-term | inhalation | systemic | 871 mg/m³ |
| Worker DNEL, | long-term | dermal | systemic | 208 mg/kg bw/day |
| Consumer DNI | EL, long-term | inhalation | systemic | 185 mg/m³ |
| Consumer DNI | EL, long-term | dermal | systemic | 125 mg/kg bw/day |
| Consumer DNI | EL, long-term | oral | systemic | 125 mg/kg bw/day |
| 64742-95-6 | Solvent naphtha (petroleum), light arom.; Low boiling point | naphtha - unspecified | | |
| Consumer DNI | EL, long-term | oral | systemic | 11 mg/kg bw/day |
| Worker DNEL, | long-term | dermal | systemic | 25 mg/kg bw/day |
| Consumer DNI | EL, long-term | dermal | systemic | 11 mg/kg bw/day |
| Worker DNEL, | long-term | inhalation | systemic | 150 mg/m³ |
| Consumer DNI | EL, long-term | inhalation | systemic | 32 mg/m³ |
| 108-32-7 | propylene carbonate | | | |
| Worker DNEL, | long-term | inhalation | systemic | 70,56 mg/m³ |
| Worker DNEL, long-term | | inhalation | local | 20 mg/m³ |
| Worker DNEL, long-term | | dermal | systemic | 20 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 17,4 mg/m³ |
| Consumer DNEL, long-term | | inhalation | local | 10 mg/m³ |
| Consumer DNEL, long-term | | dermal | systemic | 10 mg/kg bw/day |
| Consumer DNI | EL, long-term | oral | systemic | 10 mg/kg bw/day |

PNEC values

| CAS No | Substance | | |
|--|-----------------------------|------------|--|
| Environment | al compartment | Value | |
| 108-32-7 | 08-32-7 propylene carbonate | | |
| Freshwater 0,9 | | 0,9 mg/l | |
| Marine water 0,9 m | | 0,9 mg/l | |
| Micro-organisms in sewage treatment plants (STP) | | 7400 mg/l | |
| Soil 0,81 mg | | 0,81 mg/kg | |

8.2. Exposure controls



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 6 of 12





Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles:

FKM (fluoro rubber), Breakthrough time:: 480 min. NBR (Nitrile rubber), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: black
Odour: charact

Odour: characteristic
Odour threshold: not determined

Test method

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

136 - 164 °C

boiling range:

Softening point: not determined

Flash point: 29 °C DIN 53213

Flammability

Solid/liquid: not determined
Gas: not determined

Explosive properties

not determined

Lower explosion limits: 0,8 vol. %
Upper explosion limits: 6 vol. %
Auto-ignition temperature: > 200 °C
Decomposition temperature: not determined



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 7 of 12

pH-Value: not determined

Viscosity / dynamic: 3500 mPa·s

(at 20 °C)

Viscosity / kinematic: not determined
Water solubility: not applicable

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: 5 hPa

(at 20 °C)

Vapour pressure: 30 hPa

(at 50 °C)

Density: 1,03 g/cm³ DIN 51757

Relative vapour density: not determined Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion: No data available

Oxidizing properties not determined

Other safety characteristics

Solvent content: org. Lösemittel 38,8 %

Wassergehalt 0,1 %

Solid content: 62,8 %

Further InformationNo information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

No known hazardous decomposition products.

10.3. Possibility of hazardous reactions

No known hazardous decomposition products.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Print date: 04.05.2022



Safety Data Sheet

according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 8 of 12

| CAS No | Chemical name | | | | | |
|------------|---|----------------|--------------|---------------------------|--------|--------|
| | Exposure route | Dose | | Species | Source | Method |
| 64742-49-0 | Hydrocarbons, C9-C10, | n-alkanes, isc | oalkanes, cy | clics, <2% aromatics | | |
| | oral | LD50 mg/kg | 4951 | Rat | | |
| | dermal | LD50 mg/kg | 5000 | Rabbit | | |
| | inhalation (4 h) vapour | LC50 | 4951 mg/l | Rat | | |
| 64742-95-6 | Solvent naphtha (petrole | um), light arc | m.; Low boil | ing point naphtha - unspe | cified | |
| | oral | LD50 mg/kg | 3492 | Rat | | |
| | dermal | LD50 mg/kg | >3160 | Rabbit | | |
| | inhalation vapour | LC50 mg/l | >6193 | Rat | | |
| 64742-82-1 | naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha | | | | | |
| | oral | LD50 mg/kg | >15000 | Rat | | |
| | dermal | LD50 mg/kg | 3400 | Rabbit | | |
| 108-32-7 | propylene carbonate | | | | | |
| | oral | LD50 mg/kg | 33520 | Rat | GESTIS | |
| | dermal | LD50 mg/kg | > 20000 | Rabbit | GESTIS | |

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking. May cause damage to organs through prolonged or repeated exposure. (naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha)

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 9 of 12

| CAS No | Chemical name | | | | | |
|----------|---|---------------------|--|-----------------------------------|--|--|
| | Aquatic toxicity Dose [h] [d] Species Source Method | | | | | |
| 108-32-7 | propylene carbonate | | | | | |
| | Acute crustacea toxicity | EC50 > 1000 mg/l | | Daphnia magna (Big water flea) | | |

12.2. Persistence and degradability

There are no data available on the mixture itself.

| CAS No | Chemical name | | | | |
|----------|---|-------------|----|--------|--|
| | Method | Value | d | Source | |
| | Evaluation | | | | |
| 108-32-7 | propylene carbonate | | | | |
| | OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C | 83,5-87,7 % | 29 | | |
| | Readily biodegradable (according to OECD criteria). | | | | |

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|---------------------|---------|
| 108-32-7 | propylene carbonate | -0,41 |

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 10 of 12

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: Coating solution

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Marine pollutant: no
Special Provisions: 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es): 3
14.4. Packing group: III



according to UK REACH Regulation

DINITROL 4941 / CAR

Revision date: 13.04.2022 Product code: 20091 Page 11 of 12

Hazard label: 3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Tansport classification ADR/IMGD is based on packaging >30ltr(IMDG), >450ltr(ADR).

For other packaging until different classification can apply.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2004/42/EC (VOC): 38,82 %

399,8 g/l

Information according to 2012/18/EU

P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes



according to UK REACH Regulation

DINITROL 4941 / CAR

Product code: 20091 Revision date: 13.04.2022 Page 12 of 12

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,12,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data |
| STOT SE 3; H336 | Calculation method |
| STOT RE 2; H373 | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

R

| uatic Chronic 3; H412 | Calculation method |
|-------------------------------|--|
| Relevant H and EUH statements | (number and full text) |
| H226 Flamma | able liquid and vapour. |
| H304 May be | e fatal if swallowed and enters airways. |
| H319 Causes | s serious eye irritation. |
| H335 May ca | ause respiratory irritation. |
| H336 May ca | ause drowsiness or dizziness. |
| H372 Causes | s damage to organs through prolonged or repeated exposure. |

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)